

TRADITIONAL MANUFACTURER AND SUPPLIER OF GARDEN MACHINERY

DRUM MOWERS - MULCHERS - SWEEPING BRUSHES - WOOD CHIPPERS - LAWNMOWERS - LOG SPLITTERS - MODULAR SYSTEM - OTHERS





SINGLE-PURPOSE DRUM MOWERS



AGATHA DRUM MOWER

- the first VARI drum mower with the InStart technology
- up to 75 starts after battery charging
- 60 minutes for a full charge
- effortless starting with a push button



TYPE	DS-521BiS		
Engine	B&S 675 IS		
Working width	58,5 cm		
Recommended area	up to 10 000 m ²		
Area performance	1 300 m²/h		
Number of speeds	1 (2,0 kph)		
Weight	61 kg		
Article no.	4466		









Charge it

Clip it

Start

Mow



AGATHA DRUM MOWER

- VARI XP-200, Briggs&Stratton 675 Series™ or HONDA GCV 160 engine
- fixed drive axle perfectly keeps the direction even on slopes
- side screen for laying the grass into swaths
- working width of 58,5 cm/4 blades
- jaw brake of the cutting disc
- bronze worm gear in the gearbox
- innovated Optibelt kevlar V-belt
- reinforced T-Bar bracing of the blades

	ТҮРЕ	DS-521Z	DS-521B	DS-521
1	Engine	VARI XP-200	B&S 675 EXI	HONDA GCV 160
	Working width	58,5 cm	58,5 cm	58,5 cm
7	Recommended area	up to 10 000 m ²	up to 10 000 m ²	up to 10 000 m ²
	Area performance	1 300 m²/h	1 300 m²/h	1 300 m²/h
	Number of speeds	1 (2,0 kph)	1 (2,0 kph)	1 (2,0 kph)
	Weight	61 kg	59 kg	58 kg
	Article no.	4425	4400	4426

SINGLE-PURPOSE DRUM MOWERS





DOROTHA BRUSH CUTTER

- tough, resistant and innovative cover made of painted zinc coated metal sheet
- cutting disc with 4 blades (T- Bar bracing)
- independent switching of wheel and cutting drives
- precise guiding thanks to the fixed wheel drive
- big 8" arrow-shaped wheels
- height adjustment of the handlebars in 6 positions
- easy control also for women
- safety brake of the cutting disc
- hardened VARI blades
- the first brush cutter with the InStart technology
- up to 75 starts after battery charging
- 60 minutes for a full charge
- effortless starting with a push button

INSTART		NSTART
TYPE	BDR-620DH	BDR-620DBiS
Engine	HONDA GCV 190	B&S 875 IS
Working width	62,2 cm	62,2 cm
Recommended area	up to 15 000 m ²	up to 15 000 m ²
Area performance	1 900 m²/h	1 900 m²/h
Number of speeds	2 (2,0 - 2,8 kph)	2 (2,0 - 2,8 kph)
Weight	67 kg	66 kg
Article no.	4500	4501









Transport wheels
Article no.: 4241


BDR-1200 DOUBLE-DRUM MOWER

- professional double-drum mower for cutting of large areas including mountain meadows
- side and height handlebar adjustment
- big 10" wheels with tractor pattern
- directional brakes provide easy manoeuvrability of the machine
- 2 cutting discs with the working width of 120,2 cm
- 10° side swinging of the double-drum unit enables better following of the terrain
- cardan shaft connection of the cutting discs avoids blade collision
- cut grass is laid between the wheels

TYPE	BDR-1200		
Engine	HONDA GXV 390 (13 HP)		
Working width	120,2 cm		
Area performance	2 160 - 6 000 m²/h		
Number of speeds	5 + 1R (1,8 - 2,7 - 3,5 - 4,8 - 8,0 - R3,5 kph)		
Weight	200 kg		
Article no.	4242		

SINGLE-PURPOSE MULCHERS





Mulcher front cover

Article no.: 4447



- INOX stainless steel cover
- safety button avoids unmeant starting of the blade drive
- low centre of gravity, perfectly balanced
- worm gear in the gearbox
- front spur for good pass ability through the terrain
- suitable for the cutting fresh grass up to 40 cm as well
- copes with self-seeded shrubbery up to 1 cm in diameter
- adjustment of the cutting height from 4 to 9 cm
- solid GATOR mulcher blade



TYPE	F-550B	F-550
Engine	B&S 850 E	HONDA GCV 190
Working width	58 cm	58 cm
Recommended area	up to 15 000 m ²	up to 15 000 m ²
Area performance	950 - 1 300 m²/h	950 - 1 300 m²/h
Number of speeds	2 (1,8 - 2,4 kph)	2 (1,8 - 2,4 kph)
Weight	55 kg	56 kg
Article no.	4408	4380



- professional mulcher for companies and municipal services
- TUFF TORQ K-46ED hydrostatic gearbox
- automatic differential lock
- new 18" travelling wheels and new guiding wheels
- new ergonomics of the handlebars
- new replaceable shaft support of the blade and bearings
- service and safety brakes
- side opening for easier cleaning of the cutting space
- guaranteed slope accessability 30°
- professional Honda GXV 390 engine





AV-650 seat

TYPE	F-700 H			
Engine	HONDA GXV 390 (13 HP)			
Working width	70 cm			
Recommended area	unlimited			
Area performance	up to 5 440 m ² /h			
Type of gearbox	K-46ED hydrostatic gerabox with automatic differential lock FORWARD: 0-8,0 kph, BACKWARDS: 0-1,5 kph			
Article no.	4448			

SINGLE-PURPOSE MACHINES



CB-80 SWEEPING BRUSH

- compact and tough construction (total length 137 cm only)
- height adjustment of the handlebars in 6 positions
- control of all functions from the operator's place
- adjustment of the hair pressure using the washers on the front wheel (12 positions with a step of 1,6 mm)
- polypropylene sweeping hairs, round type with a diameter of 1,5 mm, outside oval 2x3 mm
- 8 spirals of the sweeping brush

ТҮРЕ	CB-80Z	CB-80
Engine	VARI XP-200	HONDA GCV 160
Working width	80 cm	80 cm
Number of speeds	1 (2,9 kph) Option: 2-speed version 2,5-3,4 kph	2 (2,5 - 3,4 kph)
Weight	55 kg	56 kg
Article no.	4442	4440



BS-80 collector

Article no.: 4445



OR-80 dozer blade

Article no.: 4451



AP-80 dust cover

Article no.: 4443



RAPIDO PLUS WOOD CHIPPER

- wood chips are perfect as a mulch layer or fuel
- worm slow-running shredder with a double-threaded spiral
- self-feeding of the crushed material into the crushing head
- transport wheels
- manipulation handle
- steel flywheel under the engine for the energy accumulation

ТҮРЕ	RAPIDO PLUS
Engine	B&S 850 E
Maximal diameter of crushed material (depends on the type, age and humidity of the crushed material)	up to 50 mm
Approximate size of wood chips	20 mm
Weight	56 kg
Article no.	4453



LUCINA MAX DRUM MOWER

- Briggs&Stratton 850 Series[™], HONDA GCV 190 or HONDA GSV 190 engine
- possible to change the cutting drum for mulching adapter, snow blade or passive sweeping brush
- patented connection with adapters
- new, tougher frame with higher torsion strength
- two travel speeds
- gear change by easy and toolless switch of the V-belt
- big 8" wheels with GRASS TRACK pattern
- possibility of unlocking the wheels for easier manipulation
- four original VARI blades
- double cutting disc with reinforced edges
- height adjustment of the handlebars in 6 positions

TYPE	BDR-620B	BDR-620	BDR-620
Engine	B&S 850 E	HONDA GCV 190	HONDA GSV 190
Working width	62,2 cm	62,2 cm	62,2 cm
Recommended area	up to 15 000 m ²	up to 15 000 m ²	up to 15 000 m ²
Area performance	1 680 m²/h	1 680 m²/h	1 680 m²/h
Number of speeds	2 (2,0 - 2,8 kph)	2 (2,0 - 2,8 kph)	2 (2,0 - 2,8 kph)
Weight	62 kg	63 kg	64 kg
Article no.	4430	4428	4457



Grooved clutch



LUCINA MAX BRUSH CUTTER

- BDR-620D Lucina MaX is equipped with an additional safety cover
- painted zinc coated metal sheet cover

BDR-620D			
HONDA GCV 190			
62,2 cm			
up to 15 000 m ²			
1 680 m²/h			
2 (2,0 - 2,8 kph)			
68 kg			
4499			





Mulcher front cover


Article no.: 4447

VM-580 MULCHER

- intended for long grass cutting and mulching, copes with older grass and thin self-seeding plants
- recommended height of cut grass 10-90 cm
- patented design of the cutting space and the guiding spur
- cutting space made of HDG metal sheet
- solid GATOR mulching blade
- possibility to add the mulcher front cover
- cutting height adjustment
- working width of 58 cm

Article no.: 4429





SP-800 SNOW BLADE

- suitable for new-fallen snow
- polypropylene sliding plates
- easy connection to the machine
- working width 79 cm

Article no.: 4450



PK-950 PASSIVE BRUSH

- continuous side adjustment
- very low dustiness while using the brush
- long lifetime of the hairs low abrasion
- easy assembly
- ideal for pavements, especially interlocking pavements and access roads
- 5 sweeping strips with polypropylene hairs
- year-round usage
- working width of 95 cm



RAPTOR HYDRO MULTIFUNCTIONAL CARRIER

- tough pressed chassis parts
- **TUFF TORQ K-46ED hydrostatic gearbox**
- automatic differential lock
- antivibration placing of handlebars
- integrated NORAM/VARI clutch
- integrated additional fuel tank with the volume of 4,5 I
- comfortable connection of the adapters
- B&S 950E engine (engine-power class 8 HP)

RAPTOR HYDRO
B&S 950 E
unlimited
K-46ED hydrostatic gearbox with automatic differential lock FORWARD: 0-8,0 kph, BACKWARDS: 0-1,5 kph
71 kg
4470



RBS-700 DRUM MOWER / RBS-700D BRUSH CUTTER

- pressed double cutting disc VARI
- 5 blades with T-Bar bracing
- working width of 70 cm
- tough pressed chassis and robust shaft support
- easy and quick connection
- RBS-700D brush cutter is equipped with an additional safety cover







RMS-600 MULCHER

- stainless steel cover of the cutting space
- working width of 60 cm
- tough pressed chassis
- **GATOR** mulching blade
- height adjustable front spur
- patented placing of the blade



ROP-115 HAY TEDDER

- working width of 90 cm
- total width of 115 cm
- hay tedding and raking
- grass aeration
- raking the fallen leaves
- option: new-fallen snow removing (using the snow blades, article no. 3758)



RSR-1000 DOZER BLADE

- continuous side adjustment
- spring suspension, with rubber edge
- zinc coated skid plate
- innovated shape of the blade
- working width of 100 cm

Article no.: 4478



AV-650 SEAT

- VARI sprung sheet-metal seat
- innovated wheels and brakes
- comfortable wide footrests
- telescopic bar
- loading capacity of 120 kg


Article no.: 4217



ANV-200 TRAILER

- loading capacity of 200 kg
- VARI sprung sheet-metal seat
- tilting body
- service and parking brakes
- reflecting glasses
- comfortable wide footrests

Article no.: 4475





SNOW CHAINS FOR 4.00-8.00 WHEELS

Article no.: 4476

WHEEL WEIGHT 2x 11,5 KG

VARI MODULAR SYSTEM – ONE ENGINE

VARI DRIVING UNITS

- ecological four-stroke engines
- low fuel consumption c. 0,8 l/h
- optimised flange and handlebars with the diameter of 25 mm
- height and side adjustment of the handlebars from the operator's place
- 80 mm automatic centrifugal clutch

weight of 23 kg



ТҮРЕ	PJXP200	PJGCV160	PJGCV190 (HONDA GSV 190)
Engine	VARI XP 200	HONDA GCV 160	HONDA GSV 190
Engine displacement	196 cm³	160 cm ³	187 cm³
Torque	10,0 Nm	9,4 Nm	11,3 Nm
Cylinder sleeve	yes	no	yes
Max. lean	20°	30°	30°
Article no.	4427	4369	4371

Rag

GEARBOX DSK-317.1/S

Number of speeds: 3+R

Article no.: 4224

DSK-31

CCESSORIES FOR

DRIVE AXLE TN-GLOBAL



Wheel size: 5.00-12

Article no.: 4367

LOOSENING DEVICE **KUK-96 / KUK-125**

LOOSENING DEVICE **KUR-70 / KUR-112**



Working width: 83 / 96 cm up to 125 cm



Working width: 60 / 70 cm up to 112 cm

Article no.: 4377 / 4378

SWING PLOUGH APH-352



Working width: 18 cm Ploughing depth: 18 cm

Article no.: 3611

ONE-WAY PLOUGH APJ-018 R/L



Working width: 18 cm Ploughing depth: 18 cm

Article no.: 3612 (R), 3635 (L)

NEW 2017

CONNECTED **DIRECTLY TO DRIVING UNITS**

WOOD CHIPPER

RAPIDO

- compatible with the VARI driving units
- wood chips are perfect as mulch laver or fuel worm slow-running shredder
- with a double-threaded spiral
- self-feeding of the crushed material into the crushing head



Recommended engine power: 3,5 - 6,5 HP Clutch diameter: 80 mm Max. diameter of crushed material: up to 50 mm Approx. size of wood chips: 20 mm

Article no.: 4449

PRESSURE WASHER

W3000V

- three different nozzles
- transport wheels
- high-quality duralumin pump
- intended for four-stroke VARI driving units with 80 mm clutch only

Max. pressure: 2 900 PSI / 200 bar Working pressure: 2 300 PSI / 159 bar Flow rate: 8,5 l/min

Article no.: 3688

ROTARY HOE RP-T2/S



Working width: 16, 22, 32, 38 cm Working depth: 2-8 cm

Article no.: 4347

AERATOR/SCARIFIER **PP-60**



Working width: 55 cm Working depth: 5 mm

Article no.: 4379

DRUM MOWER BDR-650V



Working width: 62,2 cm

FOR ALL TYPES OF WORK

INNER WEIGHT FOR THE TN-GLOBAL



4 pcs, total weight 25 kg

Article no.: 4405

COMPLETE HITCH



carrier, 33 kg weight, NZ-5/317 carrier, 2x 5 kg

NT-3



for connection and adjustment of VARI passive implements

Article no.: 3711

PASSIVE

HOE

ADJUSTING ELEMENT PLOUGHING WHEELS PK-GLOBAL



PLOUGHING GIRDLES FOR WHEELS 5.00-12"



Article no.: 4402

Article no.: 4406

FRONT WHEEL VK-GLOBAL

COVER ASSEMBLY / N-3 SHARE HOLDER WITH SHARE



Article no.: 4381

carrier (two hoes side by side) or to the N-3 share holder

to the NM1-001 potato hiller

Article no.: 3769

CULTIVATOR AKY-356



Working width: 70 cm

Article no.: 3616

SMOOTHING HARROW S-1000



Working width: 100 cm

Article no.: 3671

DIGGING SHARE AVR-453



Working depth: 12 cm

Article no.: 3618

DIGGING SHARE AVB-400



Working depth: 12 cm

NM1-001



Article no.: 3608

POTATO HILLER CARRIER POTATO HILLER SV-1







Article no.: 3608 + 2x 3609

REPLACING THE DRIVE AXLE WITH THE LOOSENING DEVICE

DRIVE AXLE

TN-GLOBAL

- 12" wheels with an arrow pattern VARI Farm Track tyres with better
- adhesion and longer lifetime comfortable control of the wheel arrestment
- the weight of the fully fitted drive axle is 95 kg
- option: ploughing girdles

LOOSENING DEVICE

GLOBAL

- original forged VARI blades
- blades width of 40 mm, thickness of 6 mm
- 2 types of blades and 2 working widths
- KUK: lanced blades, for heavy soils KUR: angular blades, for lighter, loamy-sand

MINITRACTOR VARI GLOBAL WITH SWING PLOUGH APH-352

VARI GLOBAL SETS

WITH ACCESSORIES



Article no.: 4432 + 3611 + 3710 + 3711

ACCESSORIES FOR DSK-317





TIPPING TRAILER ANV-380 Loading capacity of 380 kg

Reflecting glasses, sprung ergonomic seat, tilting body, service and parking brakes, comfortable footrests

Article no.: 3791

Article no.: 4460



Loading capacity of 400 kg Reflecting glasses, sprung ergonomic seat, 12" wheels, car tyres, strap holders

Article no.: 4410





Working width: 72 cm

Article no.: 3770

SPIKE-TOOTH HARROW BH-138 / ABR-354



Working width: 90-138 cm / 50-90 cm

POTATO PLANTER



For up to 20 kg potatoes Wheel gauge: 61 cm

Article no.: 4363

ROTARY TILLER VARI GLOBAL WITH LOOSENING DEVICE KUK-96

KUK-96 loosening device with lanced blades

of the handlebars



MINITRACTOR VARI GLOBAL WITH TRAILER ANV-400

DSK-317.1/S gearbox (speeds: 3+R)

TN-GLOBAL drive axle

height and side adjustment of the handlebars Z-01 hitch

- loading capacity of 400 kg reflecting glasses
- sprung ergonomic seat 12"wheels
- car tyres




ACCESSORIES FOR DSK-316













DSK-316/AV-650

HITCH

For all DSK-316 gearboxes without integrated hitch







BAR MOWER





Working width: 52 cm Working width: 117 cm Article no.: 4150

Article no.: 4431











Brush diameter: 37 cm Article no.: 4031

Article no.: 4458

Article no.: 3808

Article no.: 3677







Article no.: 4217

FOR TERRA-VARI

Accessories for older T-20 and DSK-317 (till 2012) gearboxes with the axle pin.



For 4-stroke VARI-HONDA engines Number of speeds: 3+R

LOOSENING DEVICE -LANCE BLADES



Working width: 95, 52-110 cm

Article no.: 4366, 3718

LOOSENING DEVICE-**ANGULAR BLADES**



Working width: 80, 25-115 cm

Article no.: 3746, 3717

DRIVE AXLE TN-01 (5x12")





CSL 484 H LAWNMOWER

- 4 in 1 mower, wheels with ball bearings
- central adjustment of the cutting height
- steel deck
- ergonomic handle, soft grip



MP1 504 B LAWNMOWER

- 4 in 1 mower, wheels with ball bearings
- central adjustment of the cutting height
- steel deck, De Luxe handle
- hose connector for quick deck washing
- EVO gearbox smooth start
- collector filling indicator



MP1 554 B LAWNMOWER

- 4 in 1 mower, wheels with ball bearings
- central adjustment of the cutting height
- steel deck, De Luxe handle
- hose connector for quick deck washing
- EVO gearbox smooth start
- collector filling indicator



MP1 554 H LAWNMOWER

- 4 in 1 mower, wheels with ball bearings
- central adjustment of the cutting height
- steel deck, De Luxe handle
- hose connector for quick deck washing
- EVO gearbox, collector filling indicator
- variable transmission with continuous speed regulation

TYPE	CSL 484 H	MP1 504 B	MP1 554 B	MP1 554 H	
Engine	HONDA GCV 160	B&S 625 E	B&S 675 EXI	HONDA GCV 190	
Working width	48 cm	50 cm	55 cm	55 cm	
Cutting height	27 – 80 mm (5 positions)	25 – 65 mm (5 positions)	25 – 80 mm (5 positions)	25 - 80 mm (6 positions)	
Bag volume	60 I	70 I	70 I	70 I	
Weight	30 kg	31 kg 35 kg		40 kg	
Article no.	3691	3692	3693	3694	



KF-140 ROTARY TILLER

- for greenhouses and small gardens
- compact and powerful tiller
- lanced blades
- conical clutch
- duralumin worm gearbox
- continuous height adjustment of the handlebars




KF-200 / KF-H160 ROTARY TILLER

- for greenhouses and middle-sized gardens
- lanced blades
- conical clutch
- duralumin worm gearbox
- height and side adjustment of the handlebars
- option: accessories for converting to the minitractor

ТҮРЕ	KF-140	KF-200 KF-H160	
Engine	VARI XP-140	VARI XP-200	HONDA GCV 160
Working width	60 cm	85 cm	85 cm
Weight	30 kg	49 kg	48 kg
Article no.	4467	4468	4469







Article no : 4484



Drive axle

432HB BRUSHCUTTER

- low weight, easy operation
- three-tooth steel cutting blade
- back harness





W3000Z PRESSURE WASHER

- three nozzles
- transport wheels
- high-pressure gun holder
- duralumin pump

TYPE	W3000Z		
Engine	VARI XP-200		
Max. pressure	2 900 PSI / 200 bar		
Working pressure	2 300 PSI / 159 bar		
Flow rate	8,5 l/min		
Weight	26 kg		
Article no.	3687		



2300W ELECTRIC CHAIN SAW

- strong electric engine and steel gearing
- automatic chain lubrication
- manual chain tension system QuickTension
- high-quality OREGON bar and chain
- safety chain brake

TYPE	2300W		
Engine	230V/50 Hz/2300W		
Bar length	40 cm (OREGON)		
Chain speed	13,5 m/s		
Oil tank volume	0,2 I		
Weight	4,7 kg		
Article no.	4329		



KP-500 / KP-700 SWIVEL LOG SAW

- heavy duty and compact construction
- direct drive from the engine
- hard metal saw blade
- cradle returning using the spring

TYPE	KP-500	KP-700
Engine	230 V / 50 Hz / 2 800 W / IP 54	400 V / 50 Hz / 5000 W / IP 54
Saw blade	505 mm	700 mm
Weight	67 kg	88 kg
Article no.	3681	3682



VARIMATIC 300 FIREWOOD PROCESSOR

- chain saw and log splitter in one machine
- easy and quick operation
- 5-8 m³ wood/hour
- automatic lubrication

VARIMATIC 300		
400 V / 50 Hz / 4000 W / IP 54 (saw) 400 V / 50 Hz / 5000 W / IP 54 (splitter		
7 t		
30 / 55 cm		
353 kg		
3686		



HORIZONTAL LOG SPLITTER VARI 5 TON

- horizontal hydraulic log splitter
- suitable for preparing wood for fireplaces
- handle and two transport wheels
- option: stand for comfortable splitting



Article	no.: 4349	
ALLIGIC	110 4040	

TYPE	5 TON SUPER FORCE
Engine	230 V / 50 Hz / 1500 W / IP 54
Splitting force	5 t
Hydraulic pressure	20 MPa
Log size	5-25 / 52 cm
Weight	50 kg
Article no.	4348

VERTICAL LOG SPLITTER VARI 7 TON, 9 TON

- robust construction
- adjustable work table
- splitting cross and wide wedge included
- option: extended wedge (9 TON, Article no. 3685)

VERTICAL LOG SPLITTER VARI 10 TON, 10 TON GAS

- **■** robust construction
- swivel table
- splitting cross and wide wedge included
- option: extended wedge (Article no. 3684)

VERTICAL LOG SPLITTER VARI 16 TON, 20 TON

- professional log splitter, robust construction
- log lift, safety frame
- attachable to the tractor power take-off (20 TON)





ТҮРЕ	7 TON SUPER FORCE	9 TON SUPER FORCE	10 TON SUPER FORCE	10 TON GAS FORCE	16 TON SUPER FORCE	20 TON SUPER FORCE
Engine	230 V / 50 Hz / 3000 W / IP 54	230 V / 50 Hz / 3150 W / IP 54	400 V / 50 Hz / 3800 W / IP 54	Zongshen 270 cm ³	400 V / 50 Hz / 5100 W / IP 54	400 V / 50 Hz / 5400 W / IP 54
Splitting force	7 t	9 t	10 t	10 t	16 t	20 t
Hydraulic pressure	15,3 MPa	25,0 MPa	19,5 MPa	19,5 MPa	27,7 MPa	22,7 MPa
Log size	12-32 / 52-104 cm	12-40 / 61-137 cm	12-40 / 59-135 cm	12-40 / 59-135 cm	max. 32 / 110 cm	max. 38 / 110 cm
Weight	115 kg	144 kg	200 kg	195 kg	264 kg	360 kg
Article no.	4274	3680	4350	3683	4423	4424

1969 1800 1969

VARI, a.s. on the basis of its inner provisions and continuous product innovations reserves the right to make changes in design and colours of the products listed in this catalogue, anytime and without prior notice, without extending the scope of its duties. It is forbidden to copy the documents and pictures in any form without consent of the publisher. Technical changes and printing errors reserved. Published by VARI, a.s.

Seller / Distributor



EUROPEAN UNION
European Regional Development Fund
Operational Programme Enterprise
and Innovations for Competitiveness

www.vari.cz/en